


## Class 125 (Standard)

# FIG. 3387

## Cored Plug



For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

### FIGURE 3387 - CORED PLUG

Nominal Size	Maximum Working Pressure▲	Dimension A	Approx. Wt. Each
<i>In. (mm)</i>	<i>PSI (kPa)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
½*	300 2065	0.94 23.87	0.10 0.05
¾	300 2065	1.07 27.17	0.17 0.08
1	300 2065	1.25 31.75	0.28 0.13
1¼	300 2065	1.36 34.54	0.44 0.20
1½	300 2065	1.45 36.83	0.62 0.28
2	300 2065	1.56 39.62	0.91 0.41

▲ – Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit [anvilintl.com](http://anvilintl.com) or contact your local Anvil Representative.

\* Part supplied as Solid Plug.

### MATERIAL SPECIFICATIONS

Dimensions: ASME B16.14

Material: ASTM A126

Finish: Black or Hot Dip Galvanized per ASTM A153 Class A

Threads: NPT per ASME B1.20.1

Agency Approvals: All cast iron threaded fittings are UL/ULC Listed and FM Approved.

▲ Pressure - Temperature Ratings in accordance with ASME B16.4 Class 125

### PROJECT INFORMATION

### APPROVAL STAMP

<b>Project:</b>	<input type="checkbox"/> Approved
<b>Address:</b>	<input type="checkbox"/> Approved as noted
<b>Contractor:</b>	<input type="checkbox"/> Not approved
<b>Engineer:</b>	<b>Remarks:</b>
<b>Submittal Date:</b>	
<b>Notes 1:</b>	
<b>Notes 2:</b>	